


### DBM 1 CI 760 FM (961 176)


- Spark-gap-based lightning current arrester with integrated backup fuse
- Maximum system availability thanks to RADAX Flow follow current limitation
- Directly coordinated with DEHNguard surge protective devices without cable length



Figure without obligation



Basic circuit diagram DBM 1 CI 760 FM



Dimension drawing DBM 1 CI 760 FM

Coordinated single-pole lightning current arrester with integrated backup fuse for 690 V TN / IT systems; with remote signalling contact for monitoring device (floating changeover contact).

Type	DBM 1 CI 760 FM
Part No.	961 176
SPD according to EN 61643-11 / IEC 61643-11	type 1 / class I
Nominal voltage (a.c.) ( $U_n$ )	690 V (50 / 60 Hz)
Maximum continuous operating voltage (a.c.) ( $U_c$ )	760 V (50 / 60 Hz)
Lightning impulse current (10/350 $\mu$ s) ( $I_{imp}$ )	35 kA
Specific energy (W/R)	306.25 kJ/ohms
Nominal discharge current (8/20 $\mu$ s) ( $I_n$ )	35 kA
Voltage protection level ( $U_p$ )	$\leq 4$ kV
Follow current extinguishing capability (a.c.) ( $I_f$ )	25 kA <sub>rms</sub>
Follow current limitation / Selectivity	no tripping of a 32 A gG fuse up to 25 kA <sub>rms</sub> (prosp.)
Response time ( $t_n$ )	$\leq 100$ ns
Max. mains-side overcurrent protection	not required
Temporary overvoltage (TOV) ( $U_T$ ) – Characteristic	1320 V / 120 min. – withstand
Operating temperature range ( $T_U$ )	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (L, N/PE(N)) (min.)	10 mm <sup>2</sup> solid / flexible
Cross-sectional area (L, N/PE(N)) (max.)	50 mm <sup>2</sup> stranded / 35 mm <sup>2</sup> flexible
For mounting on	35 mm DIN rails acc. to EN 60715 or mounting plate (using the two mounting brackets provided)
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	3 module(s), DIN 43880
Type of remote signalling contact	changeover contact
Switching capacity (a.c.)	250 V / 0.5 A
Switching capacity (d.c.)	250 V / 0.1 A; 125 V / 0.2 A; 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm <sup>2</sup> solid / flexible
Supplementary data:	-----
– Nominal discharge current (8/20 $\mu$ s) ( $I_n$ )	35 kA
Weight	908 g
Customs tariff number (Comb. Nomenclature EU)	85363090
GTIN	4013364250123
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.