



SEIL 14.5 120Q CUGALSN R25M (832 320)



Figure without obligation

Copper cable, tinned, according to EN 62561-2 for lightning protection and earth-termination systems or equipotential bonding.

| Type | SEIL 14.5 120Q CUGALSN R25M |
|---|---------------------------------|
| Part No. | 832 320 ✓ |
| Cross-section | 120 mm ² |
| Cable structure qty x Ø wire | 19 x 2.8 mm |
| Material | Cu/gal Sn |
| Average of tin layer thickness | 2 µm |
| Standard | EN 62561-2 |
| Outside diameter Ø | 14.5 mm |
| Conductivity | ≥ 52.63 m / Ohm mm ² |
| Resistivity | ≤ 0.019 Ohm mm ² / m |
| Tensile strength | 200 N / mm ² |
| Short-circuit current (a.c. 50 Hz / d.c.) (1 s; ≤ 150 °C) | 17.4 kA |
| Length tolerance | +/- 5% |
| Weight | 1,03 kg/m |
| Customs tariff number (Comb. Nomenclature EU) | 74130000 |
| GTIN | 4013364129641 |
| PU | 25 m |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Cables in different dimensions and materials are available upon request.